

# Daikin Altherma low temperature split

EHBH-CB



Guaranteed  
operation  
down to -25°C

## Wall mounted heating only air to water heat pump ideal for low energy houses

- › Perfect fit for new built as well as for low energy houses
- › Best seasonal efficiencies, providing the highest savings on running costs
- › Wall mounted indoor unit
- › Energy efficient heating only system based on air to water heat pump technology
- › Flexible configuration with respect to heat emitters
- › Possible to combine with domestic hot water
- › Outdoor unit extracts heat from the outdoor air, even at -25°C

# EHBH-CB + ERLQ-CV3/CW1




Efficiency data			EHBH + ERLQ	04CB3V + 004CV3	08CB3V / 08CB9W + 006CV3	08CB3V / 08CB9W + 008CV3	11CB3V / 11CB9W + 011CV3	16CB3V / 16CB9W + 014CV3	16CB3V / 16CB9W + 016CV3	11CB3V / 11CB9W + 011CW1	16CB3V / 16CB9W + 014CW1	16CB3V / 16CB9W + 016CW1
Heating capacity	Min.		kW	1.80 (1) / 1.80 (2)			-					
	Nom.		kW	4.40 (1) / 4.03 (2)	6.00 (1) / 5.67 (2)	7.40 (1) / 6.89 (2)	11.2 (1) / 11.00 (2)	14.5 (1) / 13.60 (2)	16 (1) / 15.20 (2)	11.2 (1) / 11.00 (2)	14.5 (1) / 13.60 (2)	16 (1) / 15.20 (2)
	Max.		kW	5.12 (1) / 4.90 (2)	8.35 (1) / 7.95 (2)	10.02 (1) / 9.53 (2)	8.6 (3) / 8.60 (4)	10.6 (3) / 10.80 (4)	11.4 (3) / 10.90 (4)	8.6 (3) / 8.60 (4)	10.6 (3) / 10.80 (4)	11.4 (3) / 10.90 (4)
Power input	Heating	Nom.	kW	0.87 (1) / 1.13 (2)	1.27 (1) / 1.59 (2)	1.66 (1) / 2.01 (2)	2.43 (1) / 3.10 (2)	3.37 (1) / 4.10 (2)	3.76 (1) / 4.66 (2)	2.43 (1) / 3.10 (2)	3.37 (1) / 4.10 (2)	3.76 (1) / 4.66 (2)
		Max.	kW	-			3.13 (3) / 4.10 (4)	4.00 (3) / 5.19 (4)	4.32 (3) / 5.22 (4)	3.13 (3) / 4.10 (4)	4.00 (3) / 5.19 (4)	4.32 (3) / 5.22 (4)
Nominal efficiency COP				5.04 (1) / 3.58 (2)	4.74 (1) / 3.56 (2)	4.45 (1) / 3.42 (2)	4.6 (1) / 2.75 (3) / 3.55 (2) / 2.10 (4)	4.3 (1) / 2.65 (3) / 3.32 (2) / 2.08 (4)	4.25 (1) / 2.64 (3) / 3.26 (2) / 2.09 (4)	4.6 (1) / 2.75 (3) / 3.55 (2) / 2.10 (4)	4.3 (1) / 2.65 (3) / 3.32 (2) / 2.08 (4)	4.25 (1) / 2.64 (3) / 3.26 (2) / 2.09 (4)

Indoor unit		EHBH	04CB3V	08CB3V / 08CB9W	11CB3V / 11CB9W	16CB3V / 16CB9W	11CB3V / 11CB9W	16CB3V / 16CB9W
Casing	Colour		White					
	Material		Precoated sheet metal					
Dimensions	Unit	HeightxWidthxDepth	890x480x344					
Weight	Unit	kg	41	43	43	44	43	44
Sound power level	Cooling		40			-		
Sound pressure level	Cooling	Nom.	26			-		

Outdoor unit		ERLQ	004CV3	006CV3	008CV3	011CV3	014CV3	016CV3	011CW1	014CW1	016CW1	
Dimensions	Unit	HeightxWidthxDepth	735x832x307			1,345x900x320						
Weight	Unit	kg	54	56		113			114			
Operation range	Heating	Ambient	Min.-Max. °CDB		-25~25			-25~35				
	Domestic hot water	Ambient	Min.-Max. °CWB		-25~35			-20~35				
Refrigerant	Type / GWP	R-410A / 2,087.5										
	Charge	kg / TCO <sub>2</sub> Eq	1.45 / 3.0	1.6 / 3.3		3.4 / 7.1						
Sound power level	Heating		61		62		64		66		66	
Sound pressure level	Heating	Nom./Silent operation	48		49		51		52		52	
Power supply	Phase / Frequency / Voltage	Hz / V	V3/1~/50/230						W1/3N~/50/400			
Current - 50Hz	Maximum fuse amps (MFA)	A	20			40			20			

(1) Condition 1: cooling Ta 35°C - LWE 18°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 35°C (DT = 5°C) (2) Condition 2: cooling Ta 35°C - LWE 7°C (DT = 5°C); heating Ta DB/WB 7°C/6°C - LWC 45°C (DT = 5°C) (3) Condition 3: heating Ta DB -7°C (RH85%) - LWC 35°C (4) Condition 4: heating Ta DB -7°C (RH85%) - LWC 45°C | Contains fluorinated greenhouse gases

**Daikin Europe N.V.** Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · [www.daikin.eu](http://www.daikin.eu) · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN15-760 03/15



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: [www.eurovent-certification.com](http://www.eurovent-certification.com) or using: [www.certiflash.com](http://www.certiflash.com)



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.